Bids are invited from for supply of items of following Physical Security Equipment for our <u>Branch-Chakaundh located in Chitrakoot Region of the Bank</u>

No	Particulars of Equipment	BIS
1	Class B Strong room door + Grill gate with clenching mechanism TRTL30. with BIS label.	IS11188
2	Emergency door B class TRTL 30 with BIS label	-DO-
3	Ventilator for TRTL 30 with BIS label.	IS14387:2005
4	Exhaust Fan	
5	V Cage with BIS label.	IS14387:2005

2. The Financial Bids in sealed cover should be submitted by 16.08.2017 up to

1600hrs (04.00PM) addressed to

The Regional Manager,
Allahabad UP Gramin Bank,
Regional Office,Amanpur
Bedi Puliya

KARWI District Chitrakoot (U.P.)-210 205.
Mob-9792203505

Email id:-chitrakoot.augb@gmail.com
or

ro.chitk@AUPGB.IN

In this context following points are to be noted:

i) The unit rate as quoted by the manufacturers should be inclusive of cost, all type of charges, transportation charge/delivery charge/taxes etc

- ii) Rates should uniformly be applicable for supply of the strong room door etc., FOR at the branch.
- iii) The rate will remain fixed for at least 6 months from the date of letter of indent.
- iv) The product should be of standard approved by BIS (Bureau of Indian Standards).

The tenderer should have a well-established and efficient service network at all major cities or near the place where the safes are to be supplied.

## Class B Strong Room Door

## Main Door

The main door should be in accordance with IS 11188: 1991 (Part I) for general specification in addition to the following:

- 1. The main door shall consist of outer and inner mild steel plates conforming to IS 2062:1992 for plates up to 15 mm thick strongly rimmed and continuously welded to form a single structure and tightly enclosing a monolithic one piece solid slab of high speed drill resisting and oxy acetylene torch resisting material that is at least 50 mm thick.
- 2. Door Frame: The doorframe should be one piece with a minimum thickness of 10 mm.
- 3. Thickness in door over locks: Should be of minimum 100mm thickness.
- 4. Locks: the door should have a minimum of 2 high precision 8 lever dual control locks.
- 5. 6. Lock Case: Should be minimum 2 step case construction covering entire jamb area.
- 7. **Bolt Work:** The bolt work should be mounted on a secure base transmitting motion to shooting bolts on both the sides.]
- 8. Automatic Relocking Device: Automatic relocking device should be fitted on the door which comes into operation if the lock is dislodged with explosives or other means.
- 9. **Grill Gate:** Grille Gate is to be hinged such that it opens inside and an unpickable dual control lock capable of operating from both sides is to be provided.

ADDITIONAL QUALIFYING CRITERIA: The tenderers should fulfill the following qualifying criteria. They shall submit copies of documents to substantiate their qualifications

along with the technical and commercial bids failing which their tenders are liable to be rejected.

- Only manufacturers are eligible to submit tenders.
- > The Tenderer should have a Registered Office and Distribution set up and should have been dealing with manufacture and supply of Strong Room Doors.
- > The Tenderer should have well established and efficient service network at all major cities or near the places where the safes are to be supplied.
- > The Tenderer shall furnish GST Registration numbers.
- > The Tenderer should be an original equipment manufacturer of locks. The lock making process should be computerized.
- > The Tenderer should be a total security solutions provider, with capability of offering Banking Security products such as Safes, Strong Room Doors and Safe Deposit Locker.

Regional Manager RO-Chitrakoot